



CONTROL SYSTEMS PTn-G Pressure Transducer Range



Pressure transducers for refrigeration applications.

- Accurate and repeatable output
- Selected and tested for refrigeration applications
- Robust design
- Rated to IP65
- Suitable for all common refrigerants including ammonia
- Seven pressure range
- Fully compensated and calibrated



Within the refrigeration environment, transducers are subjected to rapid pressure and temperature changes and have to operate in a harsh environment. JTL's PTn-G transducers have been carefully selected and tested to ensure long term accurate and repeatable readings.

Electrical connections are made inside a mini-DIN plug assembly, with integral cable glanding, to facilitate easy removal during testing and service.

The PTn-G is a high gain strain gauge device with an 1-6 V output. All devices in the range measure gauge pressure.

Technical Specification

Ambient temperature operating range	-40°C to +125°C
Height with mini-DIN plug	114 mm
Width with mini-DIN plug	47.3 mm
Height without mini-DIN plug	87 mm
Width without mini-DIN plug	27.3 mm
Electrical connections (DIN 43650)	Supply(+), Ground(-), Signal
Mechanical connections	1/8" - 27 NPT
Type	GEMS 1200

Ordering Information

PT1-G	0 to 100 psi
PT1A-G	-15 to +85 psi
PT2-G	0 to 200 psi
PT3-G	0 to 300 psi
PT35BA-G	-1 to 34 bar
PT5-G	0 to 500 psi
PT60B-G	0 to 60 bar

Doc No. 02759-PTn-G.pmd Issue 3 June 2015

JTL Systems Limited

Head Office	Newbury	tel: 44 (0)1635 263646
Technical Support Centre	Newbury	tel: 44 (0)871 3157535
Monitoring Centre	Newbury	tel: 44 (0)871 3157531