

# CONTROL SYSTEMS LCD Temperature Displays LCD10 & LCD12



## For display cabinet applications incorporating existing JTL controllers (spares / cabinet refurbishments)



- Available in a range of colours
- Durable moulded plastic design
- Clip fit mounting
- Keyswitch for controller function selection
- Incorporates case clean mode
- Suitable for display cabinet refurbishment

#### **Product Data**

The LCD10 and LCD12 displays are for use with JTL display cabinet controllers. They display the cabinet air temperature and current operating conditions together with selected alarms.

LCD12 incorporates a keyswitch facility providing upto 3 options which can be used by the allocated cabinet controller. Examples of the functions that can be available which can be set during commissioning are:

- Temperature 1 e.g. Dairy
- Temperature 2 e.g. Fresh Meat
- Case Clean Mode fans on, refrigeration off
- Non-refrigerated shelving fans off, refrigeration off

For cabinet applications incorporating new JTL controllers, please refer to LCD8, LCD9 datasheet Doc. No. 02770.

## **Technical Specification**

Display Type			LCD
Material		Moulde	ed plastic (ABS)
Cables			351 (see below)
Cutout dimensions	Height . Width	max 45 mm max 90 mm	min 43.4 mm min 88.9 mm
Display depth			25.5 mm
Operating temperature Storage temperature Humidity		0-95% (nc	0 to 60°C 25° to +85°C on-condensing)

Note these displays are not suitable for installation in the refrigerated environment.

## **Ordering Information**

### LCD10

	White	LCD10-WH	
	LCD12 (incorporates keyswitch) White Black		
Cables for use with display cabinet controllers with 7 pin DIN display connections.  LC models introduced after 1994:			
	CAB51-120		
	For display cabinet controllers with 5 pin DIN display connections EC 8	RC models and early LC models:	

CAB52-70 ...... Display extension cable 7 m

Doc No. 02771-LCD10-12.pmd Issue 2 May 2004

#### **JTL Systems Limited**

Head Office Technical Support Centre Monitoring Centre Newbury Newbury Newbury

**tel:** 44 (o) 1635 263646 **tel:** 44 (o) 871 3157535 **tel:** 44 (o) 871 3157531