



MONITORING SYSTEMS PA210 Plant Alarm Monitor



For on site and remote monitoring of up to 8 digital inputs.



- Networked product
- Provides alarms for upto 8 fault inputs
- Suitable for monitoring compressors and condensing units.
- 16 pre-defined alarm types selectable
- Set up parameters maintained for restart

Product Data

Product Features

The PA210 monitors/alarms up to 8 digital fault inputs. One of 16 pre-defined alarm types can be selected to suit most common applications.

Alarms

The PA210 provides alarm information via a JTL Network.

Remote Access

If operating within a JTL Network, alarm conditions can be viewed remotely.

Hardware

Optically isolated high voltage inputs 8

Technical Specification

For pre-defined alarm input types, please refer to Document Number 01671

Communications port RS485 2 wire
Communications data rate 4800 baud
Communications protocol JTL Jnet zone protocol

Unit dimensions (L x W x H) 247 x 98 x 51 mm
Unit weight 0.95 kg

Power supply (standard) 230 V 48-62 Hz
(Optional) 24 V, 110 V

Ordering Information

PA210 Complete unit boxed

Power Supply Options:

For 24 V append- 24 to order code
For 110 V append- 110 to order code



This unit conforms with the relevant EU standards when fitted in accordance with its installation instructions.

Doc No. 02984-PA210-datasheet.pmd Issue 2 Aug 2004

JTL Systems Limited

Head Office
Technical Support Centre
Monitoring Centre

Newbury
Newbury
Sunderland

tel: 44 (0)1635 263646
tel: 44 (0)870 321 8585
tel: 44 (0)870 321 4161