



MONITORING SYSTEMS

RL220

CPC IR-em2 Gas Leak Detection Interface



For connection of CPC gas leak detection systems to the JTL network.

- Networked product
- Fully integrated within the controls network
- Set up parameters maintained through restart



Product Data

The RL220 interface module connects the CPC IR-em2 leak detection equipment to the JTL network. Up to 31 areas can be monitored with this interface.

The leak concentration of each area is averaged over an adjustable period. The current and average concentrations are then available to the alarm system via the JTL network.

Hardware

Technical Specification

CPC communication port	RS485 2 wire
CPC communication protocol	Modbus RTU
CPC communication speed	9600 baud
Network Communications port	RS485 2 wire
Network Communications protocol	JTL Jnet zone protocol
Network Communications speed	4800 baud

Dimensions (L x W x H)	105 x 120 x 79 mm
Weight	0.31 kg

Power supply (Standard)	100-240 V 50/60 Hz
-------------------------------	--------------------

Ordering Information

RL220 for 31 areas



This unit conforms with the relevant EU standards when fitted in accordance with its installation instructions.

Doc No. 03991 RL220.pmd Issue 2 Nov 2017

JTL Systems Limited

Head Office
Technical Support Centre
Monitoring Centre

tel: 44 (0)1635 263646
tel: 44 (0) 871 3157535
tel: 44 (0)871 3157531