



CONTROL SYSTEMS

PTn-I-GC Pressure Transducer Range



Pressure transducers for refrigeration applications.

- Accurate and repeatable output
- Selected and tested for refrigeration applications
- Robust design
- Rated to IP65
- Suitable for all common refrigerants including ammonia
- Four pressure range
- Fully compensated and calibrated



Within the refrigeration environment, transducers are subjected to rapid pressure and temperature changes and have to operate in a harsh environment. JTL's PTn-I-GC transducers have been carefully selected and tested to ensure long term accurate and repeatable readings.

Electrical connections are made inside a mini-DIN plug assembly, with integral cable glanding, to facilitate easy removal during testing and service.

The PTn-I-GC is a high gain strain gauge device with an 4-20 mA output. All devices in the range measure gauge pressure.

Technical Specification

Ambient temperature operating range	-40°C to +100°C
Height with mini-DIN plug	70 mm
Width with mini-DIN plug	37 mm
Height without mini-DIN plug	47 mm
Width without mini-DIN plug	19 mm
Electrical connections (DIN 43650)	N/C, (+VE), (-VE)
Mechanical connections	1/8" - 27 NPT
Type	GEMS 3100B

Ordering Information

PT25B-I-GC	0 to 25 bar
PT35BA-I-GC	-1 to +34 bar
PT60B-I-GC	0 to 60 bar
PT120B-I-GC	0 to 120 bar

Doc No. 04509-PTn-I-GC.pmd Issue 1 June 2015

JTL Systems Limited

Head Office	Newbury	tel: 44 (0)1635 263646
Technical Support Centre	Newbury	tel: 44 (0)871 3157535
Monitoring Centre	Newbury	tel: 44 (0)871 3157531