



MONITORING SYSTEMS SS-ENERGY3-1-ADD Shop Service Energy Panel



For on site and remote electrical energy monitoring and datalogging.

- Networked product
- Set up parameters maintained for restart
- Energy totalizing
- Electrical data monitoring phase and total



Product Data

Energy Monitoring

Total kilowatt hours and average consumption over user definable periods are recorded. The SS-Energy3-1 also indicates calculated maximum demand on 30 minute intervals.

Electrical data monitoring

The electrical phase data is monitored for Voltage (V), Current (A), Power (kW), Reactive Power (kVar), Apparent Power (kVA), Power Factor (PF) and Phase angle (degrees).

The total electrical data is monitored for Power (kW), Reactive Power (kVar), Apparent Power (kVA), Power Factor (PF), Phase Angle (degrees) and Frequency (Hz).

Technical Specification

Totalizer capacity	9999999.9 kWh
Communications port	RS485 2 wire
Communications data rate	4800 baud
Communications protocol	JTL Jnet zone protocol
Unit dimensions (L x W x H)	300x 300 x 105 mm
Unit weight	4.35 kg
Power supply (standard)	230 V 48-62 Hz

Ordering Information

SS-ENERGY3-1-ADD	Additional Shop Service Energy Panel
------------------------	--------------------------------------



This unit conforms with the relevant EU standards when fitted in accordance with its installation instructions.

Doc No. 05014-SS-ENERGY3-1-ADD.pmd Issue 0 April 2018

JTL Systems Limited

Head Office	Newbury	tel: 44 (0)1635 263646
Technical Support Centre	Newbury	tel: 44 (0)871 3157535
Monitoring Centre	Newbury	tel: 44 (0)871 3157531